



SPEEDYMOTO LEGGERO BELT COVERS DUCATI MONSTER 696/796/1100

TOOLS NEEDED:

- 5mm Ball end hex tool
- 5mm T-handle hex tool

BELT COVER REMOVAL

1. Start with placing masking tape in the area above the vertical cylinder; this will keep from scratching the tank during removal.



2. Before removing the stock belt covers, find the plastic guard holding the wiring harness behind the exhaust, clip the zip tie, so this part can be easily removed (BE CAREFUL NOT TO DROP THE SPACER).

3. Remove all of the stock belt covers, the wire guard behind the exhaust and all hardware.



NEW BELT COVER INSTALLATION

1. Before installation, a small modification needs to be made to the wire guard.



2. The 2 smaller locating tabs will need to be removed so the part will fit inside the new SpeedyMoto center cover. You can do this with a pair of dykes.



3. File or shave the inside of the large single locating tab so the guard will fit into the SpeedyMoto cover. This can be done with a small file or a sharp blade.



4. Install new SpeedyMoto center cover first with the stock wiring harness guard and use the supplied hardware and a drop of blue Loctite on each bolt. ATTENTION! Be sure to capture the wiring harness with the guard so it does not touch the exhaust or interfere with the belts. Use the supplies tip ties to secure the wiring harness to the guard.

5. Now install the vertical and horizontal belt covers using new supplied hardware and a drop of blue Loctite on each bolt. Be sure the locating tabs of the new SpeedyMoto belt covers align correctly.



SPEEDYMOTO
13339 NE AIRPORT WAY, SUITE 400
PORTLAND OR 97230

ITEM NO.	DESCRIPTION	QTY.
1	Center Pulley Cover	1
2	Front Pulley Cover	1
3	Rear Pulley Cover	1
4	Dome	3
5	M6 x 40 SS Cap Screw	3
6	M6 x 25 SS Cap Screw	2

